



GENERAL NOTES:

- CSA B66 CERTIFIED FRP TANK FOR WASTE WATER.
- RATED FOR 7' OF BURIAL DEPTH AND NO TRAFFIC LOADING.
- ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN.
- SAFETY DEVICE CAN WITHSTAND 91 KG. OF DEAD LOAD.
- DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED.
- 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.



ITEM#	QTY	PART LIST	DESCRIPTION	SHELL THICKNESS: 0.500"	DRAWN: CCL/ATF
1	1	30" CAP LID W/ 8"D POLY SCREW OUT INSERT		HEMI HEAD THICKNESS: 0.650"	CHECKED: ATF
2	1	30"Ø MANWAY COLLAR	30"Ø FRP COLLAR	RIBS THICKNESS: 0.25"	DATE: MAR. 10, 2023
3	1	4" FERNCO	FLEXIBLE CONNECTOR	RIB SPACING: 17-1/4" (CL to CL)	DESIGNED: FRP
4	1	4"Ø PVC PIPE & TEEWYE	INLET	LENGTH: 11,620MM (38'-1")	APPROVED: MPS
5	2	MILD STEEL	LIFT LUGS	WORKING CAPACITY: 48,550L (10,680IG/12,816 USG)	MFG:
6	1	POLYETHYLENE SAFETY GRATE C/W HARDWARE	SAFETY GRATE	OVERALL CAPACITY: 50,384L (11,084IG/13,300 USG)	PM:
7					SALES:

CLIENT: FRP/MOCOAT		REVISION: 0	
TITLE: B11000S FIBERGLASS HOLDING TANK		SHEET: 1/1	
FRP MOCOAT FIBERGLASS LTD.		DRAWING NUMBER: B11000S	
SIZE: C	DRAWING NUMBER: B11000S	WEIGHT: 2,472 KG (5,450 LBS)	
SCALE: 1:40	BURIAL DEPTH: RATED 7'-0"		