









PLAN





ELEVATION



ELEVATION A



SECTION B



LEGEND:
TOC - TOP OF CAP LID
TOF - TOP OF FLANGE
TOP - TOP CYLINDER
BOT - BOTTOM CYLINDER
I/S - INSIDE
LL - LIQUID LEVEL
O.A.H.-OVERALL HEIGHT
O.A.L.-OVERALL LENGTH
I/S - INSIDE
O/S - OUTSIDE
Ø - DIAMETER
° - DEGREE/S
TYP- TYPICAL
CL - CENTER LINE
NTS - NOT TO SCALE

GENERAL NOTES	
- CSA ANSI/NSF 61 CERTIFIED FRP POTABLE WATER TANK.	
- RATED FOR 7' OF BURIAL DEPTH AND NO TRAFFIC LOADING.	
- ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN..	
- DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED.	
- 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.	

ITEM#	QTY	PART LIST	DESCRIPTION
1	1	30"CAP LID W/ 8"D POLY SCREW OUT INSERT, VENTED	FRP LID
2	1	30" MANWAY COLLAR	30"Ø FRP MANWAY
3	1	2" FRP NPT CONNECTION	OUTLET
4	2	CARBON STEEL LIFT LUG	LIFT LUG
5			
6			
7			

SHELL THICKNESS:	0.500"	DRAWN:	EA/CCL/ATF
HEMI HEAD THICKNESS:	0.650"	CHECKED:	MPS
RIBS THICKNESS:	0.25" WITH 1 WR	DATE:	AUG. 15, 2025
RIB SPACING:	17 1/4" CL TO CL	DESIGNED:	FRP
WEIGHT:	2,880 KG (6,350 LBS)	APPROVED:	MPS
LENGTH:	13,576MM (44'-7")	MFG.:	DS
WORKING CAPACITY:	N/A	QA:	GA
OVERALL CAPACITY:	59,644L (13,120 IG/15,744 USG)	SALES:	TA



CLIENT: FRP/MOCOAT FIBERGLASS LTD.			
TITLE: B13000W FRP POTABLE WATER TANK			
FRPMOCOAT FIBERGLASS LTD.			
SIZE: B	DRAWING NUMBER: B13000W	REVISION: 0	
SCALE: .	WEIGHT: 2,880 KG (6,350 LBS)	SHEET: 1/1	
	BURIAL DEPTH: RATED 7'- 0"		