








OPTIONAL FLANGED EXTENSION:
30"Ø X 1/4" THK X (12", 24", 30", 36", 48", 60", 72", 84") HEIGHT






EXTERIOR SURFACE LAYER
(0.13mm to 0.30mm Thick)

STRUCTURAL LAYER
(Remainder of thickness in table minus sum of
Chem, Anti-Wick, Ext Layers)

ANTI-WICKING BARRIER
(along w/chemical resistant
layer - total 2.5mm Thick)

INTERIOR
CHEMICAL-RESISTANT
LAYER (0.25mm Thick)



LEGEND:
TOC - TOP OF CAP LID
TOF - TOP OF FLANGE
TOP - TOP CYLINDER
BOT - BOTTOM CYLINDER
I/S - INSIDE
LL - LIQUID LEVEL
O.A.H.-OVERALL HEIGHT
O.A.L.-OVERALL LENGTH
I/S - INSIDE
O/S - OUTSIDE
Ø - DIAMETER
° - DEGREE/S
TYP- TYPICAL
CL - CENTER LINE
NTS - NOT TO SCALE

GENERAL NOTES

- CSA ANSI / NSF 61 CERTIFIED FRP POTABLE WATER TANK.
- RATED FOR 7' OF BURIAL DEPTH AND NO TRAFFIC LOADING.
- ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN..
- DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED.
- 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.

ITEM#	QTY	PART LIST	DESCRIPTION
1	1	30"CAP LID W/ 8"D POLY SCREW OUT INSERT, VENTED	FRP LID
2	1	30" MANWAY COLLAR	30"Ø FRP MANWAY
3	1	2" FRP NPT CONNECTION	OUTLET
4	1	CARBON STEEL LIFT LUG	LIFT LUG
5			
6			
7			

SHELL THICKNESS:	0.375"	DRAWN:	EA/ATF
HEMI HEAD THICKNESS:	0.475"	CHECKED:	MPS
RIBS THICKNESS:	0.25" WITH 1 WR	DATE:	JUL. 14,2026
RIB SPACING:	24" CL TO CL	DESIGNED:	FRP
WEIGHT:	499 KG (1,100 LBS)	APPROVED:	MPS
LENGTH:	2,794MM (9'-2")	MFG.:	TS
WORKING CAPACITY:	N/A	QA:	GA
OVERALL CAPACITY:	9,250 L (2,035 IG/2,442 USG)	SALES:	DG



CLIENT:	FRP/MOCOAT FIBERGLASS LTD.		
TITLE:	B2000W FRP POTABLE WATER TANK		
	FRPMOCOAT		
	FIBERGLASS LTD.		
SIZE:	DRAWING NUMBER:	REVISION:	
B	B2000W	0	
SCALE:	WEIGHT:	SHEET:	
.	BURIAL DEPTH:	1/1	
		RATED 7'- 0"	



B2000W FRP POTABLE WATER TANK

