


GENERAL NOTES		ITEM#	QTY	PART LIST	DESCRIPTION	SHELL THICKNESS:	0.375"	DRAWN:	EA/ATF		CLIENT: FRP/MOCOAT FIBERGLASS LTD.		
- CSA ANSI/NSF 61 CERTIFIED FRP POTABLE WATER TANK. - RATED FOR 7' OF BURIAL DEPTH AND NO TRAFFIC LOADING. - ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN.. - DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED. - 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.		1	1	30"CAP LID W/ 8"D POLY SCREW OUT INSERT, VENTED	FRP LID	HEMI HEAD THICKNESS:	0.475"	CHECKED:	MPS		TITLE: B3000W FRP POTABLE WATER TANK		
		2	1	30" MANWAY COLLAR	30"Ø FRP MANWAY	RIBS THICKNESS:	0.25" WITH 1 WR	DATE:	JUL. 14, 2026		FRPMOCOAT FIBERGLASS LTD.		
		3	1	2" FRP NPT CONNECTION	OUTLET	RIB SPACING:	24" CL TO CL	DESIGNED:	FRP				
		4	1	CARBON STEEL LIFT LUG	LIFT LUG	WEIGHT:	612 KG (1,350 LBS)	APPROVED:	MPS		SIZE:	DRAWING NUMBER:	REVISION:
		5				LENGTH:	3,759MM (12'-4")	MFG.:	TS		B	B3000W	0
		6				WORKING CAPACITY:	N/A	QA:	BR		SCALE:	WEIGHT: 544 KG (1,200 LBS)	SHEET:
7				OVERALL CAPACITY:	13,638 L (3,000 IG/3,600 USG)	SALES:	DG	.	BURIAL DEPTH:	RATED 7'- 0"	1/1		



B3000W FRP POTABLE WATER TANK

