




GENERAL NOTES

- CSA ANSI / NSF 61 CERTIFIED FRP POTABLE WATER TANK.
- RATED FOR 7" OF BURIAL DEPTH AND NO TRAFFIC LOADING.
- ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN.
- DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED.
- 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.

ITEM#	QTY	PART LIST	DESCRIPTION
1	1	30"CAP LID W/ 8"D POLY SCREW OUT INSERT, VENTED	FRP LID
2	1	30" MANWAY COLLAR	30"Ø FRP MANWAY
3	1	2" FRP NPT CONNECTION	OUTLET
4	4	CARBON STEEL LIFT LUG	LIFT LUG
5			
6			
7			

SHELL THICKNESS:	0.525"	DRAWN:	EA/ATF
HEMI HEAD THICKNESS:	0.940"	CHECKED:	MPS
RIBS THICKNESS:	0.25"	DATE:	AUG. 15,2026
RIB SPACING:	16 1/2" CL TO CL	DESIGNED:	FRP
WEIGHT:	3,356 KG (7,400 LBS)	APPROVED:	MPS
LENGTH:	21,755MM (71'-4 1/2")	MFG.:	TS
WORKING CAPACITY:	N/A	QA:	BR
OVERALL CAPACITY:	155,100 L (34,117IG/41,012 USG)	SALES:	DG



CLIENT: FRP/MOCOAT FIBERGLASS LTD.		TITLE: BX34000W FRP POTABLE WATER TANK	
SIZE: B		DRAWING NUMBER: BX34000W	
SCALE: .		WEIGHT: 6,146 KG (13,550 LBS)	REVISION: 0
		BURIAL DEPTH: RATED 7'- 0"	SHEET: 1/1



BX34000W FRP POTABLE WATER TANK

