




GENERAL NOTES:

- CSA B66 CERTIFIED FRP SEPTIC TANK.
- RATED FOR 7' OF BURIAL DEPTH AND NO TRAFFIC LOADING.
- BAFFLE WALL IS INSTALLED. VOLUMES ARE APPROXIMATE.
- ALL DRILLED HOLES FLANGES TO BE COATED WITH RESIN.
- SAFETY GRATE CAN WITHSTAND 91 KG. OF DEAD LOAD.
- DIMENSIONS SHOWN IN FEET INCHES FORMAT OTHERWISE NOTED.
- 1/2" FABRICATION TOLERANCE. DOES NOT APPLY TO LAMINATE THICKNESS.

ITEM#	QTY	PART LIST	DESCRIPTION	SHELL THICKNESS:	0.300"	DRAWN:	ATF
1	1	30" CAP LID	FPR LID	DISH HEAD THICKNESS:	0.300"	CHECKED:	
2	1	30"Ø MANWAY COLLAR	30"Ø FRP MANWAY	RIBS THICKNESS:	0.25" WITH 1 WR	DATE:	DEC 5, 2024
3	1	2" PVC-DWV SIPHON	SIPHON-O	WEIGHT:	340KG (750LBS)	DESIGNED:	
4	1	2" PVC-DWV SIPHON INSIDE ASSEMBLY	SIPHON-I	LENGTH:	3,658MM (12'-0")	APPROVED:	MPS
5	1	4"ØX12'L DWV PIPE WITH TEEWYE & FERNCO	INLET	SEPTIC CHAMBER:	4,127L (908IG/1,090 USG)	MFG:	DS
6	1	FRP FULL BAFFLE WALL W/ REINFORCEMENT	BAFFLE WALL	EFFLUENT CHAMBER:	963 L (212 IG/254 USG)	QA:	GA
7	1	POLYETHYLENE SAFETY GRATE C/W HARDWARE	SAFETY GRATE	OVERALL CAPACITY:	5,683 L (1,250 IG/1,500 USG)	SALES:	TA



CLIENT: FRP/MOCOAT FIBERGLASS LTD.

TITLE: **S1250 FRP SIPHON TANK**

FRP MOCOAT
FIBERGLASS LTD.

SIZE: **C**

DRAWING NUMBER: **S1250**


SCALE: **1:20**

WEIGHT:

BURIAL DEPTH: **RATED 7'-0"**

REVISION: **0**

SHEET: **1/1**



S1250 FRP SIPHON TANK

